



LOOSE LAY
ANTISKID

LOOSE LAY ANTISKID

THE FASTEST, CLEANEST AND MOST COST-SAVING SOLUTION FOR YOUR FLOOR

Floover Loose Lay Antiskid is a revolutionary flooring that doesn't need glue or any other fixation to the subfloor. It makes it easy and quick to install, perfect for projects for which fast installations are required. Its resistant top layer and great stability make it suitable for any kind of use, including high traffic areas.

RECOMMENDED APPLICATIONS

- Residential – living rooms, kitchens, basements
- Retail – high traffic areas
- Hospitality – rooms, public space, restaurants
- Corporate – break rooms, offices, lobbies
- Education – dormitories, student centers, classrooms
- Senior Living – all spaces within independent living properties

Floover Loose Lay Antiskid has a backing specially designed to create a suction effect, enabling a perfect adherence of every plank on the subfloor. This system makes the floor remain clean and without damage, allowing a fast, cheap and easy replacement of a single piece or the whole flooring renovation.

- No glue necessary (If glued, the recommended adhesive Mapei Ultrabond Eco Tack)
- Sound reduction without underlayment
- Easy to replace
- Heavy commercial use
- Large size format
- Microbevelled 4 sides

INSTALLATION REQUIREMENTS:

- Perfectly levelled subfloor
- Installation without dilatation joints, directly to the wall
- Fill the perimeter with silicone
- If it's installed in an open area, glue is needed to fix the perimeter
- Maximum area: 750 SQ FT, 32FT

LOOSE LAY ANTISKID

Floover Loose Lay Antiskid consists of 4 layers. The top layer is a resistant transparent PVC. This adapts perfectly to the elasticity of the vinyl below creating a nice walking surface. The third layer is made with 100% natural PVC and Fiberglass that gives a great comfort and stability. Finally it has a special antiskid underlayment that increases also the stability of the system.

TECHNICAL DATA SHEET



Microlevel 4 sides

- ① Layer of transparent PVC 0,55 mm
- ② Decor
- ③ Core layer PVC reinforced with fiberglass
- ④ Backing PVC with **micro antiskid**



Suction pad system
ANTISKID underlayment



Characteristics	Test	Loose Lay
Classification	EN 685	23/33
Dimensions	EN 427	1828,8 x 228,6 mm
Thickness	EN 430	5 mm
Weight	EN 430	9,89 kg/m ²
Abrasion resistance	EN 660-2: 99	≥ 0,015 gr/1000 r
Stain Resistance	En 438	Class 0
Fire resistance	EN 13501-1	Class BFLs1 (B1)
Dimensional Stability	EN 434	- 0,12 %
Curving	EN 434	0,5 mm
Acoustic Certification	SO 717-1	6 dB
Cigarette burn resistance	EN 438 - 2	Class 3
Flexibility	EN 435	20 mm
Slip/Slide resistance	EN 13893	DS Grade
Formaldehyde emission	EN 717	E1
UV Resistance	ISO 105	≥ Grade 6
Castor Chair	EN 425	No effect
Antistatic Performance	EN 1081	< 2 kv
Residual Indentation	EN 433	0,10 mm
Water Resistant	EN317	0% Swelling



Floover

LOOSE LAY ANTISKID


Wear layer thickness: 22 MIL
Embossing: Thin Grain
Super Coating
Pattern repeat:8x2



OZARK




BIG HORN



APPALACHIAN



BLACK HILLS



SMOKEY

	Pieces/box	ft ² /box	lb/box ²	Boxes/pallet	Weight/pallet
LOOSE LAY ANTISKID	8 pieces	24 ft ²	48.41 lb	60 boxes	2,904.60 lb

WARRANTY: LIFETIME LIMITED RESIDENTIAL, 20 YEAR LIMITED COMMERCIAL

www.floover.com

www.ecovertflooring.com

Distributed By:

MCB Products, Inc.
325 Wright Industrial Parkway
Pottersville, MI 48876

ECOVERT[®]
FLOORING COLLECTION